

Declaration of Performance (DoP)

Product Type:	Insert appliance	
Type, batch or serial number:	Jøtul C 24	
Intended use of the product:	Insert burning solid fuel without water supply	
Name and Address of the manufacturer:	Jøtul AS	
	Postboks 1411, 1602 Fredrikstad, Norway	
	Tel.: +47 69 35 90 00	
	E-mail: post@jotul.no	
AVCP: System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3	
Notified body:	Danish Technological Institute	
NB-No:	1235	
Test report no:	300-ELAB-1881-EN	
Declared performance:	1	
Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials	Minimum distances, in mm	
	Floor =	330
	Front =	1050
Risk of burning fuel falling out	Combustable materials inside the surround must becovere by insulation as decriebed in the manual No	
Emission of combustion products	со	[0,06 %]
	NOx	[119 mg/m3]
	OGC PM	[32 mgC/m3] [5 mg/m3]
Surface temperature	Pass	[06]
Electrical safety	-	
Cleanability	Pass	
Maximum water operating pressure	-	
Flue gas temperature at nominal heat output	T [295°C]	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Normal heat output	7 kW	
Room heating output	- kW	
Water heating output	-*kW	

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, September 10th 2013

(Place and date of issue)

Jon J. Berghind